Marmox Polyprofil®

Skirting and Coving Profiles

- Balconies
- ◆ Industrial Floors
- Flat roofs
- Terraces
- Car parks
- Front rendered facades

Description

Marmox Polyprofil skirting and coving profiles are prefabricated profiles for creating a permanently tight and clean floor-wall/ceiling-wall connection, for example on balconies, terraces, arcades, industrial floors and underground garages, for drywall, composite or floating screeds. Marmox Polyprofil profiles guarantee a hygienically perfect design of the floor-wall connection, as is required for floor coating in the food industry or in hospitals.

Marmox Polyprofil profiles are made from a light-coloured epoxy resin mortar with a low specific weight. The strips are manufactured in moulds without the use of separating agents. Lightweight, with high compressive and tensile strength, and extremely low water absorption, Marmox Polyprofil profiles are easy to install.

Installation

Polyprofil skirting/coving strips can be cut with a diamond cutting disc, or with a fine-toothed saw or a grinder.

Ensure that all surfaces are clean, dry, firm and free from oil and grease, before fixing using Marmox MSP360 adhesive; care must be taken to ensure that the profiles are sealed at the joints.

Marmox Polyprofil skirting/coving can be coated or painted with epoxy, polyurethane or acrylate resin based paints.

Measurements

Polyprofil profiles are supplied in 1 meter lengths.



Polyprofil profile 3/3




Polyprofil profile 3/7



Polyprofil profile 4/15 40 x 150 x 1,000 mm




Polyprofil profile 5/5




Polyprofil profile 5/10 50 x 100 x 1,000 mm



Polyprofil profile 2.5/5



Polyprofil profile 2.5/10 25 x 100 x 1,000 mm



Polyprofil profile 2.5/15 25 x 150 x 1,000 mm

